


7615-004-000 Limestone



Installation Methods



Ashlar



Herringbone

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see [www.interface.com.cn/page/disclaimer](http://www.interface.com.cn/page/disclaimer)

**Product** HN850 **Colour** Limestone **Collection** Human Nature

Product Number 7615

**Product Specifications**

Product Construction Tufted Textured Tip Sheared Loop

Yarn System 100% Recycled Solution Dyed Nylon

Dye Method 100% Solution Dyed

Soil/Stain Protection Protekt2®

Preservative Protection Intersept®

**More Product Specifications**

Machine Gauge Tapestry

Stitches 30/10cm 7.6/in

Pile Thickness 4.5mm ±0.5mm

Total Thickness 8.5mm ±0.5mm

Size Description 25\*100

Backing Structure GlasBac® RE

**Performance Specifications**

Area of Use Commercial - Heavy Use

Stability - Delaminating  
ASTM D3936 ≥ 3.0 lbs/in  
ISO 11857 ≥ 26 N  
GB/T 26843 ≥ 26 N

Stability - Dimensional  
Stability  
ISO 2551 ≤ 0.1%  
QB/T 2755 ≤ 0.1%

Stability - Tuft Bind  
ASTM D1335 ≥ 8.0 lbs  
ISO 4919 ≥ 30 N  
QB/T 1090 ≥ 24 N (QB/T 2755)

Wear - Castor Chair  
ISO 4918 ≥ 2.4  
QB/T 2755 ≤ 0.15%

Wear - Vetterman Drum  
ASTM D5252 ≥ 3.0 at 12000 cycles  
ISO 10361 ≥ 3.0 at 22000 cycles  
GB/T 26844 ≥ 3.0 at 22000 cycles

Colour Fastness to Light  
AATCC 16E ≥ 4 at 60 AFU's  
ISO 105-B02 ≥ 4-5  
GB/T 8427 ≥ 4-5

Colour Fastness to Rubbing  
and Crocking  
AATCC 165 ≥ 4  
ISO 105-X12 ≥ 4-5  
GB/T 3920 ≥ 4-5

Colour Fastness to Water  
AATCC 107 ≥ 4  
ISO 105-E01 ≥ 4-5  
GB/T 5713 ≥ 4-5

Flammability - Methanamide  
Pill  
Pass DOC FF 1-70 or ASTM D2859 Test  
ISO 6925 ≤ 25.4 mm  
GB/T 11049 ≤ 25.4 mm

|                              |                                                                                                                                           |
|------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| Flammability - Radiant Panel | ASTM E648 Class 1<br>ISO 9239-1 B1 CHF $\geq$ 4.5 kW/m <sup>2</sup> (GB 8624)<br>GB/T 11785 B1 CHF $\geq$ 4.5 kW/m <sup>2</sup> (GB 8624) |
| Flammability - Smoke Density | ASTM E662 < 450<br>ISO 9239-1 $\leq$ 750 %.min (GB 8624)<br>GB/T 11785 s1 $\leq$ 750 %.min (GB 8624)                                      |
| Antistatic                   | AATCC 134 < 3.0 kV<br>ISO 6356 $\leq$ 2.0 kV<br>GB/T 18044 $\leq$ 2.0 kV                                                                  |
| Lifetime Antimicrobial       | AATCC 174 Parts II & III 99% reduction/No mold 7 Days<br>ASTM E2471 Complete Inhibition                                                   |

### Generic Tests

|                    |                                                                 |
|--------------------|-----------------------------------------------------------------|
| Acoustic – Nylon   | Absorption Coefficient - NRC 0.0 - 0.2                          |
| Dynamic Loading    | ISO 2094 < 15% Thickness loss<br>QB/T 1091 < 15% Thickness loss |
| Static Loading     | ISO 3415 < 15% Thickness loss<br>QB/T 1092 < 15% Thickness loss |
| Green Carpet (VOC) | ASTM D5116 Accredited<br>ISO 10580 Accredited                   |
| Thermal Resistance | ASTM C518 R Value 0.5                                           |

### Environmental Specifications

|                                    |                                                                                 |
|------------------------------------|---------------------------------------------------------------------------------|
| Recycled Content %                 | 75%                                                                             |
| Pre-Consumer (Total)               | 52%                                                                             |
| Post-Consumer (Total)              | 24%                                                                             |
| Indoor Air Quality                 | Green Label Plus ASTM D5116 # GLP1354<br>UL GREENGUARD Gold UL 2818 # 71238-420 |
| NSF Sustainable Carpet             | NSF/ANSI 140 Gold Sustainable Carpet Assessment Standard                        |
| Ingredients and Life Cycle Impacts | <a href="#">Environmental Product Declaration - GlasBac® RE</a>                 |
| End of Life                        | Carpet to Carpet Recycling                                                      |
| Embodied Carbon (Cradle to Gate)   | 7.26 kg CO <sub>2</sub> eq./m <sup>2</sup>                                      |

### Technical Information

|                        |                                                                           |
|------------------------|---------------------------------------------------------------------------|
| Installation           | <a href="#">View recommended Interface Installation Guidelines online</a> |
| Maintenance            | <a href="#">View recommended Interface Maintenance Guidelines online</a>  |
| Reclamation            | View details on our ReEntry™ Program                                      |
| Warranty               | <a href="#">15 Year Standard Warranty</a>                                 |
| Manufacturing Location | ISO9001&14001&45001 Certified Plant in Taicang, China                     |