Brushed Lines

Interface[®]

A016-07 Powder



Installation Methods



All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com.cn/page/disclamer

Recycled Content %

39 %

Product Brushed Lines	Colour Powder Collection	
Product Number	A016	
Product Specificatio	ns	
	High Performance Luxury Vinyl Tile	
Wear Layer Thickness	0.55 mm	
Total Thickness (Metric)	4.5mm	
Classification	EN 651 Class 33(heavy contract) EN 651 Class 42(light industrial general)	
Finish	CERAMOR™ UV Stabilized Ceramic Bead Coating	
Acoustic Impact Noise Reduction	ISO 140.8 ΔLw = 16dB	
Nominal Dimensions	25cm x 1m	
Performance Specifi	cations	
Critical Heat Flux	AS ISO 9239-1 >7kW/m²	
Smoke Rate	AS ISO 9239-1 <750%.min	
Size, Tolerance	ISO 24342 <400 mm <0.25 mm ISO 24342 >400 mm < 0.35 mm	
Dimensional Stability	ISO 23999 <0.25%	
Thickness	ISO 24346 Average value + 0.20mm	
Resistance to Light	ISO 105-B02 ≥6	
Resistance to Heat	ASTM F1514 ΔE< 8 avg Max	
Resistance to Chemicals	EN-ISO 26987 Pass	
VOC Test	ISO 10580 Pass	
Flexibility	ISO 24344 Method A Pass	
Static Load	ASTM F970 ≤0.005' with 1500 psi	
Castor chair	ISO 4918 Pass	
Thermal Conductivity	EN 12667 0.16 W/mK	
Static Electrical	EN 1815 < 2kV	
Slip Resistance	AS 4586:2013 R10	
Environmental Spec	ifications	
Ingredients and Life Cycle Impacts	EPD for 4.5mm LVT	
NSF Sustainable Carpet	NSF/ANSI 332, Meets Certification Guidelines	
LEED V4	Contributes to IEQ: Low Emitting Materials; M&R: EPD and EPR	
Indoor Air Quality	Green Label Plus	
Pacyclad Content %	20.06	

Embodied Carbon (Cradle to Gate)	9.2 kg CO ₂ eq./m ²

Technical Information	
Installation	See Interface LVT Installation Guidelines online
Maintenance	See Interface LVT Maintenance Guidelines online
Warranty	15 Year Standard LVT Product Warranty