


F002-04 Smokey Grey




Installation Methods




Ashlar




Brick



Monolithic



Non Directional



Quarter Turn

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com.cn/page/disclaimer

Product True Earth Stones **Colour** Smokey Grey **Collection** True Earth

Product Number F002

Product Specifications

	Luxury Vinyl Plank
Wear Layer Thickness	0.55 mm
Total Thickness (Metric)	2.5mm
Classification	ISO 10582 Commercial 33
Finish	PU Coating
Acoustic Impact Noise Reduction	ISO 10140-3 $\Delta L_w = 2\text{dB}$
Nominal Dimensions	18in x 18in

Performance Specifications

Critical Heat Flux	GB 8624 (GB/T 4085 6.14.1) Pass Class B1(C)
Smoke Rate	GB 8624 (GB/T 4085 6.14.1) Pass
Size, Tolerance	GB/T 4085 6.3.1 $\pm 0.13\%$ and 0.4mm maximum GB/T 4085 6.3.3 Pass
Dimensional Stability	GB/T 4085 6.3.5 Pass
Thickness	GB/T 4085 6.3.2.1 Individual value: Average value $\pm 0.15\text{mm}$
Resistance to Light	GB/T 4085 6.12 Pass
Resistance to Heat	ASTM F1514 Pass
Resistance to Chemicals	EN-ISO 26987 Pass
VOC Test	GB/T 18586 Pass
Flexibility	GB/T 4085 6.8 Pass
Static Load	ASTM F970 1500psi
Castor chair	GB/T 4085 6.11 Pass
Static Electrical	EN 1815 <2kV
Slip Resistance	AS 4586:2013 R10

Environmental Specifications

LEED V4	Contributes to IEQ: Low Emitting Materials
Indoor Air Quality	FloorScore® CDPH 01350 certified for low VOC emissions
Recycled Content %	18 %

Technical Information

Installation	See Interface LVT Installation Guidelines online
Maintenance	See Interface LVT Maintenance Guidelines online

